Acconet Ethernet Cable: CAT5-305-SC: CAT5e 305m Solid Copper Pull-Box (UTP-Indoor)

☐ Outer Jacket: White ☐ Aluminium Foil ☑ Separator/Spline ☐ Copper-Clad Aluminium (CCA)

☑ Outer Jacket: Grey ☐ Braiding ☑ Pull-Box ☑ Solid Copper

☐ Outer Jacket: Black ☐ Drain wire ☐ Cable roll

Construction & Dimensions		
Conductor	**Material**	SC (Solid / Bare Copper)
	Size	24 AWG (4 pairs)
	Construction	1 / 0.50mm ± 0.008mm
	Resistance	≤ 9.5 Ω / 100M at 20℃
Insulation	**Material**	PE
	Avg. Thickness	0.20mm
	Min. Thickness	0.19mm
	Diameter	0.91 ± 0.03 mm
	Resistance	Min.5000 mega-Ω / km at 20℃
	Dielectric Test	1000V DC/1min; No Breakdown
Inner Layer	**Direction**	S
	Pitch	25mm Underneath
Outside Layer	**Direction**	S
	Pitch	150mm Underneath
Jacket	**Material**	PVC
	Avg. Thickness	0.55mm
	Min. Thickness	0.50mm
	Diameter	5.1 ± 0.30mm
Other	**Install Temp.**	-20°C ~ +60°C